



Standard Series

CARBON BLOCK FILTERS

Standard Series – CTO Carbon Block Filters

CBG Standard Series 100% Coconut Shell carbon block filters provide exceptional performance and capacity for a broad range of applications. The CBG Standard Series blocks are NSF Certified for Material Safety, and are the go-to block for dependable filtration solutions for OEM and Replacement Filter users.

Features and Benefits:

- Available in 10 Micron, 5 Micron, and 1 Micron formulas - Low Pressure Drop
- Minimal Fines Release for exceptional end-user confidence.
- Standard wall thickness for increased performance
- Standard Drop-In Sizing Compatible with most off-the-shelf housings
- NSF 42 Certified for Material Safety
- CA Prop 65 Compliant



These filter cartridges are tested and certified by NSF International against NSF/ANSI Standard 42 for material safety requirements only.

Specifications:

10 MICRON (NOMINAL)			
PART NUMBER	OD X L (IN.)	CHLORINE CAPACITY (GALLONS)*	PRESSURE DROP (PSI)
CBG-B10-210	2.75 x 9.8	8,000 @ 1 GPM	2 @ 1 GPM
CBG-B10-220	2.75 x 20	16,000 @ 2 GPM	2 @ 2 GPM
CBG-B10-410	4.5 x 9.8	20,000 @ 3 GPM	4 @ 3 GPM
CBG-B10-420	4.5 x 20	40,000 @ 7 GPM	6 @ 7 GPM

*Performance claims not tested or certified by NSF.

5 MICRON (NOMINAL)				
PART NUMBER	OD X L (IN.)	CHLORINE CAPACITY (GALLONS)*	PRESSURE DROP (PSI)	VOC CAPACITY (GALLONS)*
CBG-B5-210	2.75 x 9.8	10,000 @ 1 GPM	2 @ 1 GPM	500 @ 0.5 GPM
CBG-B5-220	2.75 x 20	20,000 @ 2 GPM	2 @ 2 GPM	1,000 @ 1 GPM
CBG-B5-410	4.5 x 9.8	25,000 @ 3 GPM	4 @ 3 GPM	1,500 @ 1.5 GPM
CBG-B5-420	4.5 x 20	50,000 @ 7 GPM	6 @ 7 GPM	3,000 @ 3 GPM

1 MICRON (NOMINAL)				
PART NUMBER	OD X L (IN.)	CHLORINE CAPACITY (GALLONS)*	PRESSURE DROP (PSI)	VOC CAPACITY (GALLONS)*
CBG-B1-210	2.75 x 9.8	12,500 @ 1 GPM	4 @ 1 GPM	750 @ 0.5 GPM
CBG-B1-220	2.75 x 20	25,000 @ 2 GPM	4 @ 2 GPM	1,500 @ 1 GPM
CBG-B1-410	4.5 x 9.8	30,000 @ 3 GPM	8 @ 3 GPM	2,250 @ 1.5 GPM
CBG-B1-420	4.5 x 20	60,000 @ 7 GPM	10 @ 7 GPM	4,500 @ 3 GPM

*Performance claims not tested or certified by NSF.

Operating Parameters:

- Operating Temp: 40-100°F
- Operating Pressure: 20-125 PSI

Notes:

- Performance claims are based on internal and third-party testing. Results may vary due to difference in local water quality, system design, and actual use.
- Micron ratings are Nominal.
- The contaminants or other substances removed or reduced by this water filter are not necessarily in all users' water.
- Warning:** Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before and after the system.
- The system should be flushed for approximately five minutes after installation of a new Carbon Block Filter.
- Limited Liability** - Carbon Block Guys, LLC makes no warranties of any kind, expressed or implied, statutory or otherwise, and expressly disclaims all warranties of every kind, concerning the product, including, without limitation, warranties of merchantability and fitness for a particular purpose, except that this product should be capable of performing as described in this product's data sheet.